



DX11TA COMMERCIAL

*7 ½ & 10-TON, THREE-PHASE
SPLIT SYSTEM AIR CONDITIONER
11.2 EER/13 - 13.5 IEER /R-410A*



■ **Contents**

Nomenclature.....	2
Specifications.....	3
Expanded Cooling Data.....	4
AHRI Ratings	20
Dimensions	21
Wiring Diagrams	22
Accessories	23

■ **Standard Features**

- Two-stage energy efficient compressor
- Quiet operating top discharge
- High-efficiency copper tube / aluminum fin coil
- Brass liquid and suction service valves
- High- and low-pressure switches
- Factory-installed filter drier
- Complies with ASHRAE 90.1-2016
- AHRI Certified; ETL Listed

■ **Cabinet Features**

- Innovative sound control top design
- Steel louver coil guard protects the coil from damage and adds strength to unit
- Bottom pan rails elevate unit above slab
- Heavy-gauge galvanized-steel cabinet
- Attractive Nickel Gray powder-paint finish
- When properly anchored, meets the 2010 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available.)



* Complete warranty details available from your local dealer or at www.daikincomfort.com or www.daikinac.com

	D	X	11	T	A	090	3	A	A	
	1	2	3,4	5	6	7,8,9	10	11	12	
Brand										Engineering
D - Daikin										Minor revision
Type										Engineering
X - AC R-410A										Major revision
Z - HP R-410A										
EER										Voltage
11 - 11.2 EER										3 - 208/230 V Three-Phase 60 Hz
										4 - 460 V Three-Phase 60 Hz
Compressor										Tonnage Nominal
T - Two Stage										090 - 7½ tons
										120 - 10 tons
Feature Set										
A - Base										

	DX11TA 0903A*	DX11TA 0904A*	DX11TA 1203A*	DX11TA 1204A*
COOLING CAPACITIES				
Nominal Cooling (BTU/h) ¹	93,000	93,000	120,000	120,000
EER / IEER	11.2 / 13	11.2 / 13	11.2 / 13.5	11.2 / 13.5
Decibels	84	84	84	84
COMPRESSOR				
RLA	26.9	12.0	32.6	14.8
LRA	164	94	240	130
CONDENSER FAN MOTOR				
Horsepower	1	1	1	1
FLA	5.60	3.50	5.60	3.50
REFRIGERATION SYSTEM				
Liquid Valve Connection Size ("O.D.)	5/8"	5/8"	5/8"	5/8"
Suction Valve Connection Size ("O.D.)	1 3/8"	1 3/8"	1 3/8"	1 3/8"
Valve Type	Sweat	Sweat	Sweat	Sweat
Refrigerant Charge (oz.) ²	55	55	55	55
ELECTRICAL DATA				
AC Volts	208/230	460	208/230	460
Hz / Phase	60 Hz/3	60 Hz/3	60 Hz/3	60 Hz/3
Minimum Circuit Ampacity ³	39.2	18.5	46.4	22.0
Max. Overcurrent Protection ⁴	60	30	70	35
Min / Max Volts	197/253	414/506	197/253	414/506
Electrical Conduit Size	1/2" or 3/4"	1/2" or 3/4"	1/2" or 3/4"	1/2" or 3/4"
SHIP WEIGHT (LBS)	325	325	345	340

¹ Tested and rated in accordance with ARI Standard 208/230

² Factory Holding Charge. Follow Installation Instructions for system charge

³ Wire size should be determined in accordance with National Electrical Codes; extensive wire runs will require larger wire sizes

⁴ Must use time-delay fuses or HACR-type circuit breakers of the same size as noted.

NOTES

- Always check the rating plate for electrical data on the unit being installed.
- Installer will need to supply 5/8" to 1 1/8" adapters for suction line connections.